

# Seek Shield PRO

## HANDHELD THERMAL CAMERA DESIGNED FOR LAW ENFORCEMENT.

Highly durable and easy to use, Reveal ShieldPRO combines a high-performance 320 x 240 thermal sensor with intuitive software. When you need it, a powerful 300-lumen LED light is available at the touch of a button. Reveal ShieldPRO was specifically designed for Law Enforcement Professionals. Built with a rugged over-mold housing and IP67 waterproof rating, Reveal ShieldPRO is fit to withstand the elements.

Thermal Imaging helps you safeguard land & borders, quickly clear a room, find discarded evidence at night, and track perpetrators without a flashlight. Even the most elusive suspects can't hide their heat signature.

Designed and Manufactured in Santa Barbara, California with Global Components.

### KEY FEATURES

#### 320 x 240 Thermal Sensor

Excellent image clarity and sensitivity with 76,800 pixels

#### Long-Range Detection

Detect a human at long distances in complete darkness

#### 3.5 Hour Runtime

Long-Lasting rechargeable battery

#### Waterproof Design

Designed for the outdoors with IP67 rating

#### Lightweight & Easy-to-use

Intuitive, 3 button controls provide easy operation of your camera

### BENEFITS

#### Safeguard Buildings, Land, and Borders

Military-proven surveillance technology that's affordable

#### Better Than Night Vision

Even the most elusive perpetrators can't hide their heat signature

#### Personal Safety

Clear a room without putting yourself in harm's way

#### Situational Awareness

It's a lot easier to stay safe when you can see in the dark

#### Recover Evidence

Recover discarded or hidden evidence invisible to the human eye

### TECHNICAL DATA

Thermal Sensor	320 x 240 (76,800 pixels)
Detection Distance	Up to 758 m
Field of View	24 Degree FOV
Frame Rate	>15 Hz FastFrame
Zoom	4X Digital Zoom
IP Rating	IP67 Waterproof
Display	2.4" Colour with Corning® Gorilla® GlassUncooled
Microbolometer	Vanadium Oxide
Startup Time	2-3 Seconds
Spectral Range	7.5 - 14 Microns
User Interface	Self-Contained Device with 3 Button Navigation
Detection Temp	-40 to 626F (-40 to 330C)
Storage Temp	-40 to 140F (-40 to 60C)
Operating Temp	-40 to 120F (-20 to 50C)
Runtime	Up to 3.5 Hours Thermal Imaging
Battery	Rechargeable Lithium Battery

### ACCESSORIES

- Lanyard Attachment
- Nylon Holster

